

Infosafe No™ VARAH	Issue Date : October 2024	ISSUED by HUNTERST
Product Name METHYLATED SPIRITS		

Section 1 - Identification

Product Identifier	METHYLATED SPIRITS
Company Name	Hunters Products (TAS) Pty. Ltd. (ABN 004 601 263)
Address	60 Gleadow Street INVERMAY TAS 7248 AUSTRALIA
Telephone/Fax Number	Tel: 03 6331 4755 Fax: 03 6334 1065
Emergency Phone Number	0417 744 144
Recommended use of the chemical and restrictions on use	Solvent and cleaner.

Section 2 - Hazard(s) Identification

GHS Classification of the Substance/Mixture	Flammable liquids: Category 2
Signal Word	DANGER
Hazard Statement (s)	H225 Highly flammable liquid and vapour.
Pictogram (s)	Flame



Precautionary Statement – Prevention	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P243 Take action to prevent static discharges. P280(f) Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement – Response	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P370+P378 In case of fire: Use carbon dioxide, dry chemical, and foam to extinguish.
Precautionary Statement – Storage	P403+P235 Store in a well-ventilated place. Keep cool.
Precautionary Statement – Disposal	P501 Dispose of contents/container in accordance with local regulations.
Precautionary Statement – General	P102 Keep out of reach of children. P103 Read carefully and follow all instructions.

Section 3 - Composition and Information on Ingredients

Ingredients	<u>Name</u>	<u>CAS</u>	<u>Proportion</u>
	Methylated spirits		100%

Section 4 - First Aid Measures

Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.
Skin	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. If symptoms develop seek medical attention.
Eye	If in eyes, hold eyelids apart and flush the eyes continuously with running

Infosafe No™ VARAH	Issue Date : October 2024	ISSUED by HUNTERST
--------------------	---------------------------	--------------------

Product Name **METHYLATED SPIRITS**

First Aid Facilities	water. Continue flushing for at least 15 minutes. Seek medical attention. Eye wash and normal washroom facilities.
Advice to Doctor	Treat symptomatically.

Section 5 - Firefighting Measures

Suitable Extinguishing Media	Use carbon dioxide, dry chemical, and foam.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Special Protective Equipment for Firefighters	Self-contained breathing apparatus (SCBA) required for fire-fighting personnel. If possible to do so safely, shut off fuel to fire. Use water spray to spray to cool fire-exposed surfaces and to protect personnel. Avoid spreading burning liquid with water used for cooling fire exposed containers when using water spray, boil-over may occur when the product temperature reaches the boiling point of water.
Specific Hazards Arising from the Chemical	This product is highly flammable. Keep storage tanks, pipelines, fire-exposed surfaces etc cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard. Vapours from this product may travel or be moved by air currents and be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge or other ignition sources at locations distant from the point of handling.
Hazchem Code	•2YE
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

Section 6 - Accidental Release Measures

Spills & Disposal	Wear appropriate personal protective equipment and clothing to avoid exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert non-combustible absorbent material onto spillage. DO NOT use sawdust. Use clean non-sparking tools to collect the material and place into suitable labelled containers. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.
Clean-up Methods - Large Spillages	Notify Emergency Services (Police or Fire Brigade). Tell them exact location, nature, hazards, quantities, type of vehicle and any other information that would be helpful. Contain spill. Remove all ignition sources and safely stop flow of spill. Bund area. Trained personnel should wear Personal Protective equipment as highlighted in this MSDS. Blanket the spill with foam or use water fog to disperse vapour clouds. Consult an expert regarding disposal of this product.

Section 7 - Handling and Storage

Precautions for Safe Handling	Open containers cautiously as contents may be under pressure. Use only in a well ventilated area. DO NOT store or use in confined spaces. Keep tank covered and containers sealed when not in use. Build up of mists or vapours in the atmosphere must be prevented. Avoid inhalation of vapour and mists, skin or eye contact. Do not use near welding or other ignition sources and avoid sparks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. Do not smoke. Wear appropriate protection. It is essential that all who come into contact with this material maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against

Infosafe No™ VARAH	Issue Date : October 2024	ISSUED by HUNTERST
Product Name METHYLATED SPIRITS		

physical damage. Inspect regularly for deficiencies such as damage or leaks. Always keep in containers made of the same material as the supply container. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

Section 8 - Exposure Controls and Personal Protection

Occupational Exposure Limit (OEL) Values	No exposure standards have been established for this material by the Australian National Occupational Health & Safety Commission (NOHSC). However, the exposure standards for the ingredients are stated below: Australian National Occupational Health And Safety Commission (NOHSC) Exposure Standards: <table> <tr> <th rowspan="2">Substance</th><th colspan="2">TWA</th><th colspan="2">STEL</th><th rowspan="2">Notices</th></tr> <tr> <th>ppm</th><th>mg/m³</th><th>ppm</th><th>mg/m³</th></tr> <tr> <td>Ethanol</td><td>1000</td><td>1880</td><td>-</td><td>-</td><td>-</td></tr> </table>					Substance	TWA		STEL		Notices	ppm	mg/m ³	ppm	mg/m ³	Ethanol	1000	1880	-	-	-
Substance	TWA		STEL		Notices																
	ppm	mg/m ³	ppm	mg/m ³																	
Ethanol	1000	1880	-	-	-																
Engineering Controls	TWA - the Time-Weighted Average airborne concentration over an eight-hour working day, for a five-day working week. STEL (Short Term Exposure Limit) - the average airborne concentration over a 15-minute period, which should not be exceeded at any time during a normal eight-hour workday. Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:1997 : Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.																				
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used. Type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.																				
Eye and Face Protection	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.																				
Hand Protection	Where risk of skin contact, wear nitrile or other suitable gloves conforming to AS/NZS 2161: Occupational protective gloves.																				
Body Protection	When large quantities are handled the use of plastic aprons and rubber boots is recommended. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing. When handling small quantities, normal work clothing provides sufficient protection.																				

Section 9 - Physical and Chemical Properties

Form	Liquid
Appearance	Clear, water white liquid
Odour	Characteristic alcohol odour.
Melting Point	N Av
Boiling Point	78°C
Solubility in Water	Completely Soluble
Specific Gravity	0.8
pH	Not available

Infosafe No™ VARAH	Issue Date : October 2024	ISSUED by HUNTERST
Product Name METHYLATED SPIRITS		

Vapour Pressure	44 mmHg at 20°C (ethanol)
Relative Vapour Density (Air=1)	1.59 (Air=1) (ethanol)
Evaporation Rate	2.53 (n-Butyl acetate=1) (ethanol)
Volatile Component	100%
Flash Point	13°C
Flammability	Highly flammable
Auto-ignition Temperature	392°C (ethanol)
Flammable Limits - Lower	3.5% (ethanol)
Flammable Limits - Upper	19.0% (ethanol)

Section 10 - Stability and Reactivity

Chemical Stability	Stable under normal use conditons.
Conditions to Avoid	Heat, flames, ignition sources and incompatibles.
Incompatible Materials	Chlorates, perchlorates, chromates, dichromates, nitrates and other oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

Section 11 - Toxicological Information

Acute Toxicity - Oral	LD50 (Oral, Rat): 7060 mg/kg
Acute Toxicity - Inhalation	LC50 (Inhalation, Rat): 38 mg/L/10h
Ingestion	Swallowing can cause drunkenness or harmful central nervous system effects. Effects of a small intake may include excitation, euphoria, headache, dizziness, drowsiness, blurred vision and fatigue. Severe acute intoxication may cause hypoglycaemia, hypothermia and extensor rigidity. Other effects may include decreased blood pressure, vomiting blood and blood changes. Aspiration into the lungs may cause pneumonitis.
Inhalation	Cause irritation to the respiratory tract and mucous membranes. Inhalation of the vapour may result in headache, nausea, incoordination, narcosis and vomiting. High concentrations may cause central nervous system symptoms similar to those given under ingestion below.
Skin	Can cause redness, itching and irritation.
Eye	Can be irritating to eyes. On eye contact this product can cause tearing, stinging, blurred vision, and redness.
Chronic Effects	Prolonged or repeated skin contact may cause defatting leading to dermatitis. Long term exposure by swallowing or repeated inhalation may cause degenerative changes in the liver, kidney, gastrointestinal tract and heart muscle.

Section 12 - Ecological Information

Ecotoxicity	Not severe
Persistence and Degradability	Readily Biodegradable.
Mobility	Readily dilutes with water
Environmental Fate	This substance may cause long term adverse effects in the environment

Infosafe No™ VARAH	Issue Date :October 2024	ISSUED by HUNTERST
--------------------	--------------------------	--------------------

Product Name **METHYLATED SPIRITS**

Environmental Protection Do not allow product to enter drains, waterways or sewers.

Acute Toxicity - Fish Golden ide LC0(48h): >1000 mg/L

Acute Toxicity - Daphnia Daphnia magna EC50 (24h): >1000mg/L

Section 13 - Disposal Considerations

Disposal Considerations Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Advise flammable nature. Normally suitable for disposal by approved waste disposal agent.

Section 14 - Transport Information

Transport Information Classified as a Class 3 Dangerous Good. Dangerous Goods of Class 3 Flammable Liquids, are incompatible in a placard load with any of the following: - Class 1, Class 2.1, if both the Class 3 and Class 2.1, dangerous goods are in bulk, Class 2.3, Class 4.2, Class 5, Class 6, if the Class 3 dangerous goods are nitromethane and Class 7.

ADG UN Number 1170

ADG Proper Shipping Name ETHANOL (ETHYL ALCOHOL)

ADG Transport Hazard Class 3

ADG Packing Group II

Hazchem Code •2YE

EPG Number 3A1

IERG Number 14

Section 15 - Regulatory Information

Poisons Schedule S5

Australia (AICS/AIIC) All components listed.

Section 16 - Any Other Relevant Information

Date of Preparation 29/10/2024

Literature References Preparation of Safety Data Sheets for hazardous Chemicals Code of Practice
Standard for the Uniform Scheduling of Medicines and Poisons
Australian Code for the Transport of Dangerous Goods by Road & Rail
Globally Harmonised System of classification and labelling of chemicals GHS7

Signature of Preparer/Data Service Technical Manager 0417 744 144

Technical Contact Numbers Emergency Advice All Hours:
Technical Manager: 0417 744 144 Mon-Fri 8am - 6pm
Poisons Information Centre: 13 11 26 - 24hrs
Transport/Fire Emergency: 000 (Emergency services)

Other Information This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the Workplace. Please refer to the technical datasheet (Instructions for use), and the label on the drum. The company cannot anticipate or control the individual working conditions encountered and so each user should read this SDS carefully, and if in doubt ring the Contact Point Number given below.
...End Of MSDS...

Infosafe No™ VARAH	Issue Date :October 2024	ISSUED by HUNTERST
--------------------	--------------------------	--------------------

Product Name **METHYLATED SPIRITS**

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.